

# Hot QuickCoders


## Manual Coding Worktable



Various applications



Through tabletop



Logos or text



The manual printing worktable is suitable for printing various items manually without the need for any height adjustment.

A standard HQC model is installed under the table and prints up to three lines of text in a maximum printing area of 12 x 24 mm through a cutout in the table.



Printing through table cutout with guides



Manually prints onto FILLED chip packets

The Kortho Hot Quickcoder requires very little maintenance and is simple to operate. Built up completely of corrosion-free materials, the Kortho Hot Quickcoder meets all industrial requirements and guarantees economical functioning during a long operational life.

The special Kortho Hot Inkroll gives an instant dry, sharp and clear printing result on porous and non-porous surfaces. From films and paper to glass or plastic bottles, metal cans, cardboard and much more.



Fast & convenient inkroll changes

Simply plug in a new Kortho Hot Inkroll and the Hot Quickcoder is ready to code another thousands of products. The incorporated pre-heating unit allows you to change an inkroll without any loss of production time or simply change the color of printing in a few seconds.

The type on the holder becomes flush with the top of the table or slightly higher, enabling a print on the bottom of cans, jars tins, boxes - even filled chip packets.

The table remains clear, there is no obstruction to the workflow and the operator simply adjusts the guides, loads the part and presses the footswitch for coding.



HQC mounted under the table

Fixed texts or separate characters can be placed on the interchangeable textplates. The textplate can be exchanged within seconds.

### TECHNICAL SPECIFICATIONS

Maximum printing area (mm)	12 x 20 or 12 x 24 mm
Maximum printing speed (prints/min)	300
Product Speed (metres/min)	60
Power supply	230VAC ± 10% 50-60 Hz, optional 115VAC ± 10% 50-60 Hz
Air supply	5 - 8 bar (clean, dry, oilfree)
Power rating (Watts)	110
Operating pressure (bar)	4 (56 PSI)
Air consumption (max litres per cycle)	0,3 at 4 bar
Noise level (dB)	82
Maximum temperature textplate °C	90 °C
Main dimensions (mm) coding unit	L 163,5 - W 115, - H 255
Main dimensions (mm) controlbox	L 310, - W 125, - H 300
Total weight Coding unit/controlbox (kg)	2 / 2,3
Control system	Microprocessor controlled control unit
Kortho Hot inkroll standard	Non-toxic black, blue, red, green, white, yellow, brown.
Industrial standards	CE

In the light of continuous development and improvement Korthofah reserves the right to modify the specifications of the models without giving prior notice.

For further information contact:



**Trend Marking Systems**  
 PO Box 1311 Castle Hill NSW 2154  
 TEL: 02 96299535 FAX 02 96297535  
 EMAIL: trend@trendmarking.com.au  
[www.trendmarking.com.au](http://www.trendmarking.com.au)